

# Towards broadband global optical and wireless networking

Marian Marciniak

**Abstract**—This paper presents a novel, non-conventional approach to the future optical and wireless hybrid transport network, capable of supporting/dominant kinds of traffic, i.e., voice/real time, wireless and packet data traffic in a single transport network. The proposed model combines different technologies as connection and connectionless networks, optical cable and wireless (microwave/millimetre wave or optical wireless), being suitable for a variety of purposes and services in order to achieve global broadband networking features. Our new networking model contains an extension to wireless world in order to achieve mobility and personalisation of connection. From the networking point of view it consists of an upgrade of real-time traffic with the microwave modulated optical wave, in order to carry out conventional mobile wireless signals via optical fibres over long distances and without significant distortion. The whole available bandwidth can be fully exploited in the hybrid network. In the IP part of the network the quality of service (QoS) can be differentiated for various classes of packets and network reliability/survivability can be categorised for the whole hybrid network. This proposal combines complete and revolutionary shift to packet traffic with smooth evolutionary upgrades. We believe the model presented here is a powerful tool to trace the future evolution of telecommunications worldwide for the next 25 years.

**Keywords**—optical and wireless networking, radio-over-fibre, optical packet networks, transparent networks.

## 1. Introduction

Global broadband networking is a crucial requirement for the future information society, which needs a seamless personal access to broadband services, everybody to anybody, from any location to any destination, anytime. The technology of conventional connection-oriented voice networks has been developed for a hundred of years already and is in a mature state. Terabit per second transmission via optical fibre links is a reality with the use of asynchronous transfer mode/synchronous digital hierarchy (ATM/SDH) over wavelength division multiplexing (WDM) technologies. In addition, the transparent optical transmission at distances of thousands of kilometers become a reality with the advent of optical amplifiers.

Although the optical fibre communications still faces a number of technological difficulties and physical constraints with chromatic dispersion (CD), polarisation mode dispersion (PMD) and nonlinear optical interactions as classical examples, it is still the best technology to achieve terrestrial global networking. However, a serious drawback

of that technology is the lack of mobility features, so in this paper a suitable combination of optical and wireless technologies is addressed and discussed.

It is worth to underline that actually the basic concept of networking is a subject of revolutionary change from classic circuit switched, connection – oriented networks to modern packet switched, connectionless transmission of data [1]. In fact this is driven by the dramatic expansion of Internet users worldwide. Therefore circuit-switched networks which work excellent for voice traffic and in general for real-time traffic are not at all a suitable solution for packet data traffic.

Packet traffic is the basis of Internet. It has a statistic nature, so at certain moments of time and network points the flow of data might be much higher that the network equipment is able to handle. This means that some data have to be stored in buffers, and if available buffer capacity is insufficient, then some data have to be sacrificed. This affects the quality of service provided by the network. This statistical phenomenon is called “burst of packets” and has provoked an effort to search for suitable means to cope with it [2]. For some applications this is not a critical situation, as the missing data can be retransmitted. But usually retransmission is not allowed for real-time voice or video services. Nevertheless, even when the networks are over-provisioned, i.e., with potential performance characteristics much better that actually needed, one could easily imagine an immense and impossible to handle data flow generated by computer viruses or malicious attacks, and a complete blocking of the network might result from that.

New technologies are being proposed to enable successful real-time service transmission through packet network [3]. However, even generally accepted, IP protocol is not so obvious as the only future platform for a converged voice/data network. In fact the main problem to be resolved is the lack of QoS guarantees for real-time traffic inherent to this approach.

In this paper we propose a combination of different technologies, such as connection and connectionless networks, optical cable and wireless (microwave/millimetre wave or optical wireless), suitable for a variety of purposes and services in order to achieve global broadband networking features. In addition to our recent proposal of a hybrid connection and connectionless networks superimposed on the top of a physical WDM layer, and on different optical wavelengths, our new network model contains an extension to wireless world in order to achieve mobility and personalisation of the connection. From the network point of view it contains an upgrade of real-time traffic with the microwave

modulated optical wave, in order to carry out conventional mobile wireless via optical fibres over long distances and without a significant distortion.

The paper is organised as follows: Section 2 discusses the optical fibre communication technologies, while Section 3 addresses the relevant characteristics of the wireless mobile world. In Section 4 the hybrid optical and wireless networking basis are laid out. Conclusions and future work are summarised in Section 5.

## 2. Optical fibre communication technology

The transparent features of the network will be discussed in detail, pointing out that that “transparent” and “all-optical” does not mean necessarily the same [4]. The impact of optical transparency on a successful deployment of future optical packet switched networks is discussed. Actually the opacity of a network is considered as resulting from conversion to electronics only. However, an “optical opacity” is inherent to several all-optical solutions, too. Indeed, the optical transparency has to be sacrificed in future optical logic elements, e.g., for signal processing, packet switching, etc. Implementation of networking functions with photonic components is summarised and directions of future development are pointed out. Finally, a novel non-conventional approach to voice + IP network is presented in the concluding part of the paper.

### 2.1. Optical transparency

The advent of erbium-doped fibre amplifiers which replaced electronic regenerators in fibre transmission links in early 90s resulted in optical transparency of the links [5]. The evolution of actual telecommunication networks towards transparent networks started at that time. Transparent networks at regional and global scale with transmission speed exceeding one terabit-per-second became a reality. Such networks are commonly referred to as “terabit networks” [6].

The notion of transparency of a transmission link (not necessarily optical) is much older than optical fibre communications. Its primary meaning is that the output signal is proportional to the signal at the input of a link. Consequently, the transparency is rather an analogue feature, apparently contrary to modern digital transmission schemes.

An ideal transparency is not realisable in an optical network, since even an ideal glass fibre exhibits attenuation, chromatic dispersion of the first and higher orders, and optical nonlinearities. Moreover real fibres exhibit polarization mode dispersion (PMD), resulting from random local lack of circular symmetry of the fibre due to manufacturing imperfections and local stresses caused by cable structure. Those features of a fibre result in distortion, crosstalk, and noise in the transmitted optical signal.

Transparent photonic network insures the scalability, i.e., possibility of future upgrades. Wavelength becomes a new degree of freedom (wavelength-switched and routed networks), and can be switched in wavelength routers and converters.

The lack of an ideal transparency requires very high wavelength precision and stability of optical sources in a dense WDM network, which considerably increases the cost of the devices. Therefore, the goal is not to lose the precious wavelength. The solution is to keep the signal in optical domain while it traverses as large part of the network as possible, and this is why transparency is so important.

Transparent network still includes attenuation and/or amplification, and eventually wavelength conversion of signals. Transparent wavelength conversion assumes conservation of temporal signal shape, superimposed on a different wavelength.

In a way transparent networks go back to the analogue age. Transparent components of the optical network treat the passing signals in an analogue way. The transparency length is a distance over which the signal can be transmitted successfully. Transmission over longer distances requires some form of regeneration. The transparency length depends on number of factors, and it can be increased in the future, when the technology is sufficiently developed.

Moreover, the expected introduction of optically transparent fibre links to subscriber networks will allow to take advantage from WDM technology also in that area. New ways of providing access are emerging to satisfy the need for interactive broadband services. A combination of various signals (i.e., analogue or digital radio and television, interactive broadband services, Internet traffic) could then be transmitted simultaneously. The emphasis is on the possibility to transmit conventional wireless radio signal. What is really very important, is that the transparent optical networks are scaleable, i.e., provide a potential for future upgrades [7].

### 2.2. Optical switching and routing

Degrees of freedom of an optical network are:

- 3-D space co-ordinates;
- time (and resulting possibility of optical time domain multiplexing – OTDM);
- wavelength (WDM);
- polarization of light.

Those provide opportunities for optical switching in space, time, wavelength, and polarisation domains. In addition to that, logical on/off switching may be implemented in optical logic elements.

Optical routing can be realised as wavelength routing in a transparent way as:

- an analogue and passive solution or
- an analogue and active solution with wavelength conversion.

### 2.3. All-optical opacity

All-optical packet routing involves some intelligence of the router and decisions based on the information included in the packet. Therefore it is not realisable in transparent way. Even though all-optical routing concept involves optical logics, optical memory, etc., it is not optically transparent and it exploits optically opaque elements. The signal remains in optical domain, but due to digital operations the fundamental transparency condition of proportionality between output and input signals is not satisfied.

Emerging evolution directions of optical network infrastructure and its include migration:

- from circuit switched optical networks, with analogue processing of carrier frequency, i.e., in spectral domain, where the transparency is a positive characteristics;
- to a packet switched network, with direct digital processing of signals in time domain, realizing all-optical switching and in particular exploiting optically opaque all-optical routing devices.

A combination of transparency exploitation in wavelength domain and all-optical logic in time domain seems to be the most justified way of network evolution.

## 3. Wireless mobile world

Wireless technology has been developed during the last decade for the mobile networks. New frequency bands are exploited in view of transmission capacity and reliability, the 60 GHz band being an example. Sophisticated 3G and beyond broadband and interactive services are foreseen in many countries in the near future. European telecom companies have invested a lot of money in the UMTS licenses. Unfortunately, it is still not obvious when the investment will bring the expected revenues.

While microwave and millimeter wave links have excellent mobility characteristics that is impossible to achieve with other transmission media (wireless optical links have very poor performance compared to microwave ones), they still suffer from a number of constraints, most of them resulting from electromagnetic compatibility (EMC) re-

quirements, in order to avoid interference and crosstalk. Also the wireless links suffer from the attenuation of signal due to air characteristics, weather, smog, and the local shape of terrain or trees and buildings. The line of sight between the transmitter and receiver is usually an essential requirement for reliable transmission. Microwave spectrum is expensive and limited. Fibre optic technology can help to transmit wireless signal superimposed on the optical wavelength, as we have proposed and analysed recently [8].

## 4. Hybrid optical and wireless networking

Among real time services the voice is still dominant. As videophone is concerned, this technology is not likely to be accepted widely in the near future. In fact people even prefer short message system (SMS) to spare bandwidth, time and money. Television broadcasting will never be done via public telecom networks as well.

Attempts to transmit voice over IP have an inherent difficulty to guarantee quality of service [9] – in fact nobody guarantees anything, as the basis of Internet is a “best-effort” principle. So “real-time” in fact stops to be “real” in packet traffic. Recently we have proposed to stop to care so much about voice traffic which is already an excellent developed technology, and to start to think about separate voice and data networks [10]. We propose a hybrid network in which voice is carried on dynamically allocated wavelengths, according to an instantaneous demand for real-time service traffic. Table 1 shows a comparison of main features of both types of traffic in a hybrid network [11].

Our non-conventional approach consists of voice (and other real-time services) subnetwork implemented within data traffic network. Voice is transmitted via circuit-switched subnetwork, while IP traffic travels in a packet-switched connectionless network. The two kinds of traffic are separated and interleaved in frequency (wavelength) domain, not in time domain.

The conventional mobile microwave/millimetre wave signal transmission can be included in the transparent real-time part of the network by the means of modulating the optical carrier wavelength with the mobile signal [12]. Then it can be transmitted over long distances via fibres before being detected at an optical receiver and processed further.

The network intelligence has to be located at IP routers and has to provide the real-time subnetwork including microwave transmission on a sufficient number of wavelengths [13]. This approach allows to profit fully from both SDH/ATM technology – best suited for real time-circuit switched services, and from IP protocol – developed uniquely for packet-switched traffic. Moreover, the QoS can be differentiated for various classes of services [14].

Table 1  
Voice versus Internet traffic

Characteristics	Voice, real-time	Internet, data
Bandwidth	Dedicated on demand	As wide as available
Basic principle	Circuit-switched	Packet-switched
Packet length	Constant	Variable
Quality of service	Guaranteed	Best-effort
Lost packets	No retransmission	Retransmitted
Traffic	Deterministic	Statistic
Other	Instantaneous bandwidth (# of wavelengths) controlled logically in IP routers	Intelligence
	Transparent	Includes all-optical opacity
Access	Conventional twisted-pair access to public exchange offices	Broadband access to servers, e.g., via cable-TV or mobile

## 5. Conclusions and future work

The novel non-conventional approach to the future hybrid network retains the well-developed voice technology with transparent transmission. Voice traffic is carried via dynamically allocated wavelengths in conventional way as circuit-switched traffic. The number of wavelengths is controlled by IP layer according to the instantaneous demand for real-time traffic. All remaining wavelengths are available for the IP traffic, which becomes free of real-time restrictions and can adopt variable-packet length, no idle bits, and best-effort scheme. As a consequence, the whole available bandwidth can be fully exploited in the hybrid network. In the IP part of the network, the quality of service can be differentiated for various classes of packets and network reliability/survivability can be categorised for the whole hybrid network.

The terms “all-optical network” and “transparent network” are not equivalent. After a decade of triumph of transparent WDM transmission, evolution towards optical packet-switched networks appears to be imminent. All-optical network requires optically opaque (i.e., not transparent) optical solutions. Opaque all-optical elements have to be introduced in the all-optical packet switched network. Those optically opaque elements will perform all-optical signal processing in general, and all-optical routing functions in particular.

Voice and IP traffic have fundamentally different characteristics and requirements which should not be overlooked and have to be taken into account when designing basics of future real-time service and IP converged network. On the other hand, the future development of converged network should not lose the well developed voice traffic technology with ATM and SDH.

The approach presented here is a result of in-depth investigation of different networking principles and traffic schemes, and physical constraints that characterise the classical fixed fibre network and new mobile wireless world. This proposal substitutes the complete and revolutionary shifting to packet traffic that a number of people foresee, with a smooth evolution and network upgrade. What is really worth to note is that real time traffic provides security and network availability, conserving a number of connections even in an malicious attack occurs. So we believe the model presented here is a powerful tool to trace the future evolution of telecommunications worldwide for the next 25 years.

## Acknowledgements

Numerous and very profitable interactions with partners from European Projects: the NEXWAY Network of Excellence, *Advanced Infrastructure for Photonic Networks* (COST 266), *Reliability of Optical Components and Devices in Communications Systems and Networks* (COST 270), and *Towards Mobile Broadband Multimedia Networks* (COST 273), as well as with the ITU Study Group 15 *Optical and Other Transport Networks*, and IEC Technical Committee 86 *Fiber Optics* are warmly acknowledged. This research is being supported by the State Committee for Scientific Research under grants 632/E-242/SPB/COST/T-11/DZ198/2003-2005 and 632/E-242/SPB/COST/T-11/DZ 311/2003-2005.

## References

- [1] M. Marciniak, “From circuit- to packet-switched or to hybrid network?”, in *5th Int. Conf. Transp. Opt. Netw. ICTON 2003, Worksh. All-Opt. Rout.*, Warsaw, Poland, 2003, vol. 1, pp. 47–50.

- [2] S. Bjørnstad, C. M. Gauger, M. Nord, E. Baert, F. Callegati, D. Careglio, W. Cerroni, J. Cheynts, D. Colle, P. Demeester, C. Develder, D. R. Hjelme, G. Junyent, M. Klinkowski, M. Marciniak, M. Kowalewski, M. Lackovic, M. Pickavet, C. Rafaelli, J. Sole-Pareta, N. Stol, E. Van Breudegem, and P. Zaffoni, "Optical burst switching and optical packet switching", in *COST 266 Final Report*. Croatia: University of Zagreb, 2003, pp. 115–154.
- [3] D. Wright, "Voice over MPLS compared to voice over other packet transport technologies", *IEEE Commun. Mag.*, vol. 40, no. 11, pp. 124–132, 2002.
- [4] M. Marciniak, "Transparent versus opaque issues in an all-optical packet switched network", in *10th Int. Worksh. Opt. Waveg. Theory Numeric. Modell.*, Nottingham, UK, 2002.
- [5] M. Marciniak, "Optical transparency and optical opacity in future all-optical packet switched network", in *XXVIIth Gener. Assemb. Int. Union of Radio Sci. URSI 2002*, Maastricht, NL, 2002.
- [6] M. Marciniak, "The impact of optical transparency on the successful development of all-optical terabit networks", in *5th World Multi-Conf. Syst., Cyber. Inform. SCI 2001*, Orlando, USA, 2001.
- [7] M. Marciniak, "Reliability aspects of the future hybrid optical network and quality of service issues for real time and packet traffic", in *Proc. Int. Conf. Advanc. Optoelectron. & Lasers CAOL 2003*, Alushta, Ukraine, 2003, vol. 1, pp. 63–68.
- [8] L. Smoczyński and M. Marciniak, "A comparison of different radio over fibre system concepts with regard to applications in mobile Internet and multimedia access", in *XXVIIth Gener. Assemb. Int. Union of Radio Sci. URSI 2002*, Maastricht, NL, 2002.
- [9] M. Marciniak, M. Kowalewski, and M. Klinkowski, "Advanced optical infrastructure for the emerging optical internet services", in *SSGRR 2002s-Int. Conf. Advanc. Infrastr. e-Business, e-Education, e-Science, and e-Medicine on the Internet*, L'Aquila, Italy, 2002, book of abstracts, pp. 82–83.
- [10] M. Marciniak, "Towards hybrid real-time & photonic packet network", in *Conf. Opt. Internet & Austr. Conf. Opt. Fibre Technol. COIN/ACOFT 2003*, Melbourne, Australia, 2003, pp. 461–464.
- [11] M. Marciniak, "Broadband optical and wireless networking for personal information services", in *7th Int. Conf. "Evolution of telecommunication transport networks. Construction, development and management"*, Partenit, Ukraine, 2004.
- [12] L. Smoczyński and M. Marciniak, "Radio-over-fibre 60 GHz broadband access", in *Int. Topic. Meet. Microw. Photon. MWP 2003, Nefert. Worksh. Broadband Opt. Wirel. Access*, Budapest, Hungary, 2003.
- [13] N. Geary, A. Antonopoulos, and J. O'Reilly, "Analysis of the potential benefits of OXC-based intelligent optical networks", *Opt. Netw. Mag.*, vol. 4, no. 2, pp. 20–31, 2003.
- [14] M. Klinkowski and M. Marciniak, "Services differentiation in MPLS photonic packet networks", in *5th IFIP Work. Conf. Opt. Netw. Des. Modell. ONDM 2003*, Budapest, Hungary, 2003, vol. 1, pp. 283–290.



**Marian Marciniak** Associate Professor has been graduated in solid state physics from Marie-Curie Sklodovska University in Lublin, Poland, in 1977. From 1985 to 1989 he performed Ph.D. studies in electromagnetic wave theory at the Institute of Fundamental Technological Research, Polish Academy of Sciences, followed

by Ph.D. degree (with distinction) in optoelectronics received from Military University of Technology in Warsaw. In 1997 he received his Doctor of Sciences (habilitation) degree in physics/optics from Warsaw University of Technology. From 1978 to 1997 he held an academic position in the Military Academy of Telecommunications in Zegrze, Poland. In 1996 he joined the National Institute of Telecommunications in Warsaw where he actually leads the Department of Transmission and Fibre Technology. Previous activities have included extended studies of optical waveguiding linear and nonlinear phenomena with analytic and numerical methods including beam-propagation methods. Actual research interests include photonic crystal technology and phenomena, optical packet-switched networks, and the future global optical and wireless network. Recently he has introduced and developed a concept of a hybrid real-time service end photonic packet network. He is an author or co-author of over 190 technical publications, including a number of conference invited presentations and 13 books authored, co-authored and/or edited by himself. He is a Senior Member of the IEEE – Lasers & Electro-Optics, Communications, and Computer Societies, a member of The New York Academy of Sciences, The Optical Society of America, SPIE – The International Society for Optical Engineering and its Technical Group on Optical Networks, and of the American Association for the Advancement of Science. In early 2001 he originated the IEEE/LEOS Poland Chapter and he has served as the Chairman of that Chapter until July 2003. He is widely involved in the European research for optical telecommunication networks, systems and devices. He was the originator of accession of Poland to European Research Programs in the optical telecommunications domain, in chronological order: COST 240 *Modelling and Measuring of Advanced Photonic Telecommunication Components*, COST P2 *Applications of Nonlinear Optical Phenomena*, COST 266 *Advanced Infrastructure for Photonic Networks*, COST 268 *Wavelength-Scale Photonic Components for Telecommunications*, COST 270 *Reliability of Optical Components and Devices in Communications Systems and Networks*, COST 273 *Towards Mobile Broadband Multimedia Networks*, and very recently two new starting actions COST 288 *Nanoscale and Ultrafast Photonics* and COST P11 *Physics of Linear, Nonlinear and Active Photonic Crystals*. In all but two those projects he acted as one of the originators at the European level. He has been appointed to Management Committees of all those Projects as the Delegate of Poland. In addition, he has been appointed as the Evaluator of the European Union's 5th Framework Program proposals in the Action Line *All-Optical and Terabit Networks*. He is a Delegate to the International Telecommunication Union, Study Group 15: *Optical and Other Transport Networks*, and to the International Electrotechnical Commission, Technical Committee 86 *Fibre Optics* and its two sub-Committees. He served as a member of Polish Delegation

to the World Telecommunication Standards Assembly WTSA 2000. From 2002 he participates in the work of the URSI – *International Union of Radio Science, Commission D – Electronics and Photonics*. In 2000 he originated and actually serves as the Chairman of the Technical Committee 282 on *Fibre Optics* of the National Committee for Standardisation. Since May 2003 he serves as the Vice-President of the Delegation of Poland to the Intergovernmental Ukrainian-Polish Working Group for Cooperation in Telecommunications. He is the originator and the main organiser of the *International Conference on Transparent Optical Networks ICTON* starting in 1999, and a co-located events the *European Symposium on Photonic Crystals ESPC* and *Workshop on All-Optical Routing WAOR* since 2002. He is the Technical Program Committee Co-Chair of the *International Conference on Advanced Optoelectronics and Lasers CAOL*, and he participates in Program Committees of the *Conference on the Optical Internet & Australian Conference on Optical Fibre Technology COIN/ACOFT*, the *International Conference on Mathematical Methods in Electromagnetic Theory MMET*,

the *International Workshop on Laser and Fiber-Optical Network Modeling LFNM*, and the *International School for Young Scientists and Students on Optics, Laser Physics and Biophysics/Workshop on Laser Physics and Photonics*. He serves as a reviewer for several international scientific journals, and he is a Member of the Editorial Board of *Microwave & Optoelectronics Technology Letters* journal, Wiley, USA, and the *Journal of Telecommunications and Information Technology*, National Institute of Telecommunications, Poland. Languages spoken: Polish (native), English, French, and Russian. His biography has been cited in *Marquis Who's Who in the World*, *Who's Who in Science and Engineering*, and in the *International Directory of Distinguished Leadership of the American Biographical Institute*.

e-mail: M.Marciniak@itl.waw.pl

e-mail: marian.marciniak@ieee.org

Department of Transmission and Fibre Technology

National Institute of Telecommunications

Szachowa st 1

04-894 Warsaw, Poland